

ROANOKE COUNTY COMMUNITY DEVELOPMENT COMMERCIAL FIRE SUPPRESSION SYSTEM SUBMITTAL CHECKLIST

Project Name:		Date:
Occupancy Address:		
Owner:		Telephone:
Occupant/Tenant:		Telephone:
Owner's Address:		
Designer: (print)	s	Signature
Address:		
Telephone:	Fax:	Email:
accordance with the cur adopted standards.* Inf following applicable iter 1 Floor plans dimension the locations of all we enclosure and partition when penetrated by	frent edition of the Uniformation on shop draws, and please mark oned showing, in plan votalls and/or partitions. ions and how the rated equipment and/or wiring	out, and installation is to be done in niform Statewide Building Code and all rawings should include all of the N/A where appropriate: Tiew, locations and spacing of all devices, and Please indicate construction of the protected assemblies will be maintained ng, per IBC section 712
construction of build and suspended ceilir	tion, full height or schei ing floor/ceiling asseml ng.	matic diagram, including location of blies above and below, raised access floor
 Type of agent being used by brand name and chemical nomenclature; please include design extinguishing or inerting concentration of mixture as applicable Description of occupancies and hazards being protected, designating whether or not the enclosure is normally occupied 		
6 Description of the agent storage containers used including internal volume, storage pressure and nominal capacity expressed in units of agent mass, or volume at standard conditions of temperature and pressure		
 Description of nozzle(s) used including size, orifice port configuration, and equivalent orifice area Description of pipe and fittings used including material specifications, grade and pressure rating 		

- 9. ___ Description of wire or cable used including classification gauge (AWG), shielding, number of strands in conductor, conductor material and color-coding schedule.

 Segregation requirements of various system conductors shall be clearly indicated. The required method of making wire terminations shall be detailed
- 10. __ Description of the method of detector mounting
- 11. ___ Equipment schedule or bill of materials for each piece of equipment or device showing device name, manufacturer, model or part number, quantity and description
- 12. ___ Plan view of protected area showing enclosure partitions (full and partial height); agent distribution system including agent storage containers, piping, nozzles; type and location of pipe hangers; detection, alarm, and control system including all devices and schematic wiring interconnection between them; end-of-line device locations; location of controlled devices such as dampers and shutters; location of instructional signage
- 13. ___ Isometric view of agent distribution system showing the length and diameter of each pipe segment; node reference numbers relating to the flow calculations; fittings including reducers and strainers; orientation of tees, nozzles including size, orifice port configuration, flow rate and equivalent orifice area
- 14. ___ Details of each unique rigid pipe support configuration showing method of securement to the pipe and to the building structure¹
- 15. __ Manufacturer's data sheets on all equipment used in the system. Where manufacturer's data sheets over multiple devices, indicate those devices used in the system.
- 16. __ Complete step-by-step description of the system sequence of operations including functioning of abort and maintenance switches, delay timers, and emergency power shutdown
- 17. __ Complete calculations to determine volume and quantity of agent and capacity of backup batteries, if necessary. Flow calculations shall be performed in accordance with approved engineering methods prescribed by the appropriate standard. The system shall be within the manufacturer's listed limitations

¹Piping hanging supports in areas with a seismic design category of other than A or B must be reviewed and approved by the registered design professional in accordance with IBC section 1621 and ASCE 7, section 9.6.

²Fire protection system design is considered engineering work and must be done under the supervision of the design professional of record, where applicable with State Law. Fire alarm shop drawings must first be submitted to the design professional, where applicable and stamped "approved" prior to submittal to our office. For more information please see the SFPE Position Statement; *The Role of the Engineer and the Technician Designing Fire Protection Systems* at

http://www.sfpe.org/upload/sfpe position statement october 2005 001.pdf

*Currently adopted edition of applicable standards for general design/installation:

- International Building Code 2003; International Fire Code 2003
- NFPA 11-1998 Low Expansion Foam
- NFPA 11A-1999 Medium- and High-Expansion Foam
- NFPA 12-2000 Carbon Dioxide Extinguishing Systems
- NFPA 12A-1997 Halon 1301 Fire Extinguishing Systems
- NFPA 16-1999 Installation Foam-Water Sprinkler & Foam-Water Spray Systems
- NFPA 2001-2000 Clean Agent Fire Extinguishing Systems